



**Composition**

100% PA 6.6 + PU COATED

**Fabric properties**

Usable width	.	150,0 CM
Full width	Full width	153,0 CM
Weight with a deviation of 5%	EN 12127 meth 5	350 G/M <sup>2</sup>

**Mechanical properties**

Shrinkage wash 60°C warp ISO 6330 6N+F	ISO 5077 2007	< 3,0 %
Shrinkage wash 60°C weft ISO 6330 6N+F	ISO 5077 2007	< 3,0 %
Tensile strength warp	ISO13934-1 2013	3000 N
Tensile strength weft	ISO13934-1 2013	3000 N
Tear Strength trousershape warp	ISO13937-2 2000	230 N
Tear Strength trousershape weft	ISO13937-2 2000	280 N
Abrasion 12kPa	ISO12947-2 1998	> 100 000 CYCLI
Spraytest	ISO 4920 2012	100 ISO 5
Watercolumn	EN20811/ISO811	>10 000 MM
Oil repell AA	AATCC 118	6

**Colourfastness**

		Light	Middle	Dark	Change
Colourfastness to washing 40°C	ISO105C06 2010			4	
Colourfastness to dry cleaning	ISO105D01 2010			4	
Colourfastness to rubbing dry	ISO105X12 2016			4	
Colourfastness to rubbing wet	ISO105X12 2016			4	

**Washing symbols**



**Remarks**

Remark	-	WATERCOLUMN AFTER 1 X 60° ISO 6330
Remark	-	> 4 000MM